



SHENZHEN YUCHIP LIGHTING CO.,LTD

Email: manager@yuchip.com Website: www.yuchip-led.com

LED DANCE FLOOR



LED Dance Floor Feature:

Floor LED display use durable die-casting structure, high wear resistance resin mask, so you can put it on the ground and walk on it. The overall seal design, IP65 waterproof, quick disassembly of the modular design , they makes install and maintain be simpler. The product in the application add virtual software interactive technology can have extremely powerful function to create extraordinary superior effect of simulate scene.



SHENZHEN YUCHIP LIGHTING CO.,LTD

Email: manager@yuchip.com

Website: www.yuchip-led.com



Stage LED Dance Floor

The Module Structure, Seamlessly Create, Height Adjustable.

Closely Seal Heat Dissipation Design

Complete elimination of moire phenomenon by closely seal heat dissipation design, IP65 waterproof, and unique spot spray treatment.



High Brightness

Gray grade is more than 13bit, high brightness can be get 3500nits, colorful and vivid display effect, good quality SMD chip, bigger beam angle, better watched effect.



HIGH COLOR REPRODUCTION

VGA synchronization technology, screen display content is the same with computer, easy to change the display videos or pictures.



SUPER HIGH WEIGHT BEARING CAPACITY

Super high weight bearing capacity
Which can easily support a car
driving though them. Weight bearing
capacity of one cabinet as high as
2150KG, weight bearing Capacity
of one square meter as high
as 2.5 T.





SHENZHEN YUCHIP LIGHTING CO.,LTD

Email: manager@yuchip.com Website: www.yuchip-led.com

APPLICATIONS

Floor LED display widely used in hall ,square, showroom, stage, bar, shopping malls, catwalks. It can be used for fixed installation and rental events.





Parameter:

Product Model	P3.91	P4.81	P6.25	P6.4	P8.9	P10.4
Pixel pitch	3.91	4.81	6.25	6.4	8.9	10.4
Module size	250*250			256*256	250*250	
Cabinet resolution dot	128*128/128*256	104*104/104*208	80*80/80*160	80*80	56*56/56*112	48*48/48*96
Cabinet size	500*500/500*1000			512*512*115	500*500/500*1000	
Material	PC mask, iron case, aluminum case					
Scanning way	1/16 scan			1/13 scan	1/8 scan	
Bearing kg/m ²	750					
Weight kg/m ²	55					
Grey grade	16384					
Refresh frequency HZ	800-1920					
Brightness cd/m ²	≥2500cd	≥5000cd		≥1000cd		≥1200cd
Horizontal vertical angle	140°					
Radian	Inner arc 15°					
Front/Rear IP Level	IP45	IP65	IP45			
Interactive equipment	human-computer interaction					
Interactive communication	interactive software					