
Explosion Proof 6 Foot Extension Cord with Inline Switch - 15 amp continuous service EPEXC-6-ILS



EPEXC-6-ILS Explosion Proof Extension Cord

Amp Rating:15 amp Continuous Service

Dimensions:Cord length-6 Feet Plug-2.78"-L 1.75"-W

Configuration: 2 Pole 3 Wire

Suitable Plug Cable Diameter: .538" to .639"

Wiring: 6` 14/3 SOOW Cable Terminated w/ (1) 20 Amp Receptacle and In-Line Switch - (1) 5-15P Explosion Proof Straight Blade Plug

Voltage: 125 Volts

Receptacle Specs:1 In-Line Receptacle

Configuration: 2 Pole 3 Wire

Materials: Copper Free Aluminum

Dimensions: 3"-W X 5.69"-D X 6.13"-H

Mating Plugs: ****[EPP-15A](#), [EPP-20-A](#)****

Finish: Epoxy Powder Coat

Switch Specs:

Configuration: Front Mounted Switch

Materials: Malleable Iron - Copper Free Aluminum

Dimensions: 3"-W X 4.69"-D X 5.38"-H

Finish: Triple-Coat—(1) zinc electroplate, (2) chromate, (3) epoxy powder coat

[U.L. Certification](#)

Plug / Outlet Certifications

Class I Div 1 Groups C and D

Class II Div 1 Groups E, F and G

Special Orders- Requirements

Contact us for special requirements

Toll Free: 1-800-369-6671

Intl: 1-903-270-1187

E-mail: sales@larsonelectronics.com

Links (Click on the below items to view):

- [Addpic1large](#)
- [Addpic2large](#)
- [Addpic3large](#)
- [Addpic4large](#)
- [large](#)
- [Manual](#)
- [medium](#)
- [HigResPic1](#)
- [HigResPic2](#)
- [HigResPic3](#)
- [HigResPic4](#)
- [HigResPic5](#)
- [HigResPic6](#)
- [HigResPic7](#)