
**1/3 HP Explosion Proof Portable Ventilation Exhaust Fan - C1D1/C2D1 - 120V - 1650 CFM - 15'
Cord w/ EXP Cord Cap
EPF-VFP-10-120V-NFK-15C-16.3-EPP**



EPF-VFP-10-120V-NFK-15C-16.3-EPP Explosion Proof Exhaust Fan

Listing: United States, Canada

Unit Type: Portable Explosion Proof Ventilation Exhaust Fan

Dimensions: 12" x 14.9" x 14.17"

Weight: 33 lbs

Voltage: 120V AC

Startup Amps: 5.2A

Motor: 1/3 HP

RPM: 3600 RPM

CFM: 1650 CFM

Power Factor: 0.76

Noise: 66 dB

Switch: On/off, External

Inlet: 10" (Duct Not Included)

Operating Temperature Range: -

Temperature Rating: T3B

Materials: Non-sparking/Non-metallic (Fan Blades), Steel (Body)

Mount: Portable w/ Carrying Handle, Rubber Feet

Cord: 15' 16/3 SOOW Cord w/ EXP Cord Cap

Cord Cap Options: 5-15P or 5-20P

Color: Safety Orange

Ratings

Class I, Divisions 1 & 2 Groups C,D

Class II, Divisions 1 & 2 Groups E,F,G

IP54

Weatherproof Fan

T3B Temp Rating

External Grounding Lug

Duct Not Included

Special Orders- Requirements

Contact us for special requirements

Phone: 1-214-616-6180

Toll Free: 1-800-369-6671

Fax: 1-903-498-3364

E-mail: sales@larsonelectronics.com

Options:

EPF-VFP-10-120V-NFK-15C-16.3-EPP-Cord Cap

Example: EPF-VFP-10-120V-NFK-15C-16.3-EPP-1523

Cord Cap	
5-15	-1523
5-20	-2023-125V

Links (Click on the below items to view):

- [addpic1large](#)
- [addpic2large](#)
- [addpic3large](#)
- [addpic4large](#)
- [large](#)
- [medium](#)
- [SpecSheet](#)
- [HigResPic1](#)
- [HigResPic2](#)
- [HigResPic3](#)
- [HigResPic4](#)
- [HigResPic5](#)