


**Explosion Proof Fixture/Extension Cord Plug - 15 Amp Rated - 6ft SOOW w/ Blunt Cut End**Part #: [EPP-15A-6FT-BCE](#)**Larson Electronics EPP-15A-6FT-BCE Explosion Proof Plug with 6ft SOOW Cable and Blunt Cut End**

The EPP-15A-6FT-BCE explosion proof plug is rated at 15 amps and along with our with our EPP-20A series plug is compatible with our EPO-20A explosion proof 20 amp outlet. This plug can be used in both regular 120V outlets and T style outlets although in order to retain explosion proof safety, it must be mated to an explosion proof outlet. This plug is designed to lock into compatible twist lock receptacles by twisting the plug body until an audible click is heard, which indicates the plug is securely connected. Once locked into place this plug will not accidentally pull out. This C1D1 plug comes factory installed with 6` of 16/3 SOOW cable and a blunt cut end.

This plug is watertight and ideal for applications where moisture and corrosion is a problem and well suited for use in marine and manufacturing environments. This plug is rated Class 1, Division 1 and 2 and Class 2, Division 1 and 2 and is suitable for use in areas where petrochemical vapors may be present. This explosion proof plug features non sparking aluminum construction, a longer housing for easy handling, specially designed brass pins for secure full length pin contact, and a 15 amp current rating.

[Click Photo to Enlarge](#)

**Inter-Compatibility:** These plugs will fit non-explosion proof standard receptacles (NEMA 5-15R, 5-20R, or 6-20R). These plugs are cross-interchangeable with Crouse Hind™ ENP general purpose plugs and will work with Crouse Hind™ ENR Dead Front Receptacles. Any equipment requiring these C-H plugs should work with the EPP-15A-6FT-BCE plugs. Due to possible manufacturer changes we cannot guarantee interchangeability although we have made every effort to ensure cross compatibility correctness.

**Suggested Applications:** Manufacturing, Industrial, Warehouse, Lighting, Motor-Generator Sets, Compressors, Wet areas or Locations Where Petrochemical Vapors are Present.

#### **Specifications / Additional Information**

##### **EPP-15A-6FT-BCE Explosion Proof Plug**

**Amp Rating:** 15

**Dimensions:** 2.78"-L 1.75"-W

**Configuration:** 3 Pole 2 Wire

**Suitable Cable Diameter:** .538" to .639"

**Seals:** Neoprene Plug Wire Bushing

**Wiring:** 6` 16/3 SOOW - Blunt Cut End

**Comparability:** EPO-20A Receptacle- Crouse Hind™ ENR Receptacles

**Cross Interchangeability:** Crouse Hind™ ENP General Purpose Plugs

**Protection:** Twist Lock Activation on Compatible Twist Lock Receptacles

##### **Certifications - Compliance**

Class 1, Div 1 & 2 Groups B,C,D

Class 2 Div 1 & 2 Group G & Coal Dust

Class III

CSA Type 7BCD, 9G

##### **Special Orders- Requirements**

Contact us for special requirements

**Toll Free:** 1-800-369-6671

**Fax:** 1-903-498-3364

**E-mail:** sales@larsonelectronics.com

[Scroll Down to Purchase-](#)

[This product does not qualify for free shipping.](#)

[Part #: EPP-15A-6FT-BCE \(222532\)](#)





Links (Click on the below items to view):

- [Hi-Res Image 1](#)
- [Hi-Res Image 2](#)
- [Hi-Res Image 3](#)
- [Hi-Res Image 4](#)