



1GAU-HB-2X150LED-RT - High Bay LED Light

1#000000Lamp Type: Cree LED
1Dimensions:1 27.85"L x 16.07"W x 16.76"H
1Weight: 167 lbs
1Voltage: 1100-277 Volts AC, 50/60Hz or 11-25 Volts AC/DC
1Total Watts:1 300W
1Lumens:1 35,000
1Luminous Efficacy: 1116.67 Lm/W
1Lamp Life: 160,000+ Hours
1Color Temp:1 5000K, 4000K, 3000K
1Color Rendering Index:1 >75 CRI
1Beam Angle:1 60° or 125°
1Lighting Configuration: 1Flood Pattern
1Power Efficiency:1 >95%
1Power Factor:1 10.992
1Amp Draw:1 2.5A @ 120V, 1.25A @ 240V, 1.08A @ 277V, 12.5A @ 24V
1Ambient Operating Temp Range:1 -50° C to +85°C
1Operating Temp Rating:1 T5
1Housing Material:1 Copper Free Cast Aluminum
1Housing Finish:1 Epoxy Powder Coated - Grey
1Lens Material:1 Hardened Borosilicate Glass
1Gasket Material:1 Silicone
1Mounting:1 Swivel Mount or Pendant Mount
1Wiring Hub:1 3/4" NPT
1LED Driver Specs
1Input Voltage: 1100-277 Volts AC
1Input Current: 13.6A Max
1Output Voltage: 154V Max
1Output Current: 14.2A

1Ratings

1Certified to UL 844 Ed. 13
1Certified to UL 1598
1Certified to C22.2 No. 137 Rev 2009
1Certified to C22.2 No. 250.0
1Certified to C22.2 No. 30-M-1986 Rev 2012
1T5 Temperature Rating
1ABS Type Approved
1IEC 60529 Tested
1IP67 Rated Waterproof
1LEL Approved
1Multiple Driver Banks
180% Lumen Retention after 60,000 Hours
1Factory Sealed Light Fixture
1Field Serviceable
1Recommended 15' to 40' Mounting Height
1Weatherproof

1Special Orders- Requirements

1Contact us for special requirements
1Phone: 11-214-616-6180
1Toll Free: 11-800-369-6671
1Fax: 11-903-498-3364
1E-mail: 1sales@larsonelectronics.com

Options:

-Voltage-Beam Angle-Color Temp

Example: -1227-60DB-50K

Voltage	
120-277V AC	-1227
11-25V AC/DC	-1224

Beam Angle	
60°	-60DB
125°	-125DB

Color Temp	
5000K	-50K
4000K	-40K
3000K	-30K

Links (Click on the below items to view):

- [Addpic1large](#)
- [Addpic2large](#)
- [Addpic3large](#)
- [Addpic4large](#)
- [large](#)
- [medium](#)
- [HigResPic1](#)
- [HigResPic2](#)
- [HigResPic3](#)
- [HigResPic4](#)
- [HigResPic5](#)
- [HigResPic6](#)
- [HigResPic7](#)
- [HigResPic8](#)
- [HigResPic9](#)
- [HigResPic10](#)