

**60W Flameproof LED Linear Fixture - 100-250V AC - (2) 30W LED Lamps - ATEX/IECEx  
ATEX-HALP-48-2L-LED-2X30W-R1-220V**



**ATEX-HALP-48-2L-LED-2X30W-R1-220V Flameproof LED Light**

**Listing:** International, European Union

**Lamp Technology:** LED

**Dimensions:** 51.57" x 8.7" x 5.7" (1310mm x 222mm x 145mm)

**Lamp Quantity:** 2

**Weight:** -

**Voltage:** 100V AC - 250V AC

**Frequency:** 50/60 Hz

**Total Watts:** 60W

**Single Lamp Watts:** 30W

**Total Lumens:** 4,959 lms

**Single Lamp Lumens:** 2,480 lms

**Luminous Efficacy:** 100 lm/W

**Lamp Life:** 50,000+ Hours

**Color Temperature:** 5700K

**Color Rendering Index:** >75

**Lamp Type:** -

**Lamp Base:** -

**Replacement Lamp:** -

**Beam Angle:** -

**Lighting Configuration:** Flood Pattern

**Power Efficiency:** -

**Power Factor:** >0.95

**Amperage:** 0.5A @ 120V, 0.25A @ 240V

**Ambient Operating Temp Range:** -25°C to +50°C/+55°C

**Operating Temp Rating:** T6

**Housing Material:** Glass Fiber Reinforced Polyester

**Housing Finish:** -

**Lens Material:** UV Resistant Polycarbonate

**Gasket Material:** Foam

**Mount:** -

**Terminals:** (2) L1, L2, L, N, PE - 0.39" (10mm)

**Hub Quantity:** 1

**Hub Size/Location:** (1) 1.5" (M25) @ Side

**Stopping Plugs:** (2) 1.5" (M25) Molded Plastic/Polyamide

**Ratings/Approvals**

ATEX/IECEx Rated

Zone 1/Zone 2

Zone 21/Zone 22

Ex db eb mb op is q IIC T6/T5 Gb

Ex tb IIIC T80°C/T85°C Db

IP66

**Special Orders- Requirements**

Contact us for special requirements

**Toll Free:** 1-800-369-6671

**Intl:** +01-903-498-3364

**Fax:** 1-903-498-3364

**E-mail:** [sales@larsonelectronics.com](mailto:sales@larsonelectronics.com)

Links (Click on the below items to view):

- [large](#)
- [medium](#)
- [SpecSheet](#)
- [HigResPic1](#)