



◆ **FEATURES**

- Reduce energy consumption and operating costs by 70% or more
- Maintenance free operation - lasts up to 10 to 20 times longer than conventional lighting
- No UV or IR and no RF interference
- Environmentally friendly - fully recyclable, no mercury or other hazardous material
- Listed on the DLC Qualified Products List



Emium SL2 LED High Bay Fixture

Emium SL2 High Bay fixtures are ideal for commercial buildings, factories, warehouses, gymnasiums, etc.

Our SL2 features high quality components from industry leading manufacturers (Philips LEDs and Meanwell driver) for superior performance and longevity. The housing is constructed of AL1070 (high thermal conductivity), 99.7% pure aluminum for superior heat dissipation.

Photometric studies and analysis show that the performance of our 100W LED high bay meets the illumination from a 400W metal halide HID high bay...using less than 30% of the energy.

Their IP65 rating make them impervious to the elements (water, dust, insects, etc.).

We carry a complete line of products to meet all types of commercial needs. Our products are engineered to install very simply and make the transition from HID or fluorescent lighting very cost-effective.

100,000 hrs rated life

5 Year Warranty



emium


emium lighting, see differently

for more information email info@emium.com

or call 224.735.3435 | www.emium.com

SPECIFICATIONS

| Model | EL-HD-HB100 | EL-HD-HB150 | EL-HD-HB200 |
|-------------------------|---|------------------------|------------------------|
| Power (watts) | 100 | 150 | 200 |
| Lumen Output | 13,000 or 14,000 | 19,500 or 21,000 | 26,000 or 28,000 |
| Beam Angle | 60° 90° 120° | | |
| Input Voltage | 100-277VAC or 200-480VAC | | |
| CRI | > 84 R _a | | |
| Color | 3000K | 4000K | 5000K 6000K |
| Physical Specifications | Dimensions: Diameter - 11" Height - 7.8" Weight: 10.7 lbs. | | |
| Housing | Cast 1070 99.7% aluminum with black or white powder coat finish High transparency tempered glass | | |
| Operating Temperature | -30°F to 150°F | | |
| Protection | Over voltage, over current, over temperature Shut down with auto-recovery | | |
| Waterproof Rating | IP65 | | |
| Dimmable | Yes 0 - 10V (optional) | | |
| Accessories | Prismatic transparent PC hood Aluminum reflector Wire guard Occupancy sensor (motion) Daylight sensor (photocell) | | |
| Rated Life | 100,000 hrs | | |


emium
emium lighting, see differently

 for more information email info@emium.com

 or call 224.735.3435 | www.emium.com